

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
16 June 2005 (16.06.2005)

PCT

(10) International Publication Number  
**WO 2005/054708 A1**

(51) International Patent Classification<sup>7</sup>: **F16G 1/28**

(74) Agents: KODAMA, Yoshihiro et al.; Enju-Ochanomizu Bldg. 3F, 17-2, Sotokanda 2-chome, Chiyoda-ku, Tokyo 101-0021 (JP).

(21) International Application Number:  
PCT/JP2004/018109

(22) International Filing Date:  
30 November 2004 (30.11.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2003-403239 2 December 2003 (02.12.2003) JP

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (for all designated States except US): BANDO CHEMICAL INDUSTRIES, LTD. [JP/JP]; 2-15, Meiwa-dori 3-chome, Hyogo-ku, Kobe-shi, Hyogo 652-0883 (JP).

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicants and


(72) Inventors (for US only): MATSUDA, Kiyotaka [JP/JP]; c/o BANDO CHEMICAL INDUSTRIES, LTD., 2-15, Meiwa-dori 3-chome,, Hyogo-ku, Kobe-shi, Hyogo 652-0883 (JP). OOTA, Takashi [JP/JP]; c/o BANDO CHEMICAL INDUSTRIES, LTD., 2-15, Meiwa-dori 3-chome,, Hyogo-ku, Kobe-shi, Hyogo 652-0883 (JP).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD FOR PRODUCING HELICAL SYNCHRONOUS BELT, AND HELICAL SYNCHRONOUS BELT PRODUCED BY SAME



(57) Abstract: To develop a helical synchronous belt for driving carriage that does not generate tracking due to the effect of helical teeth, in order to prevent lower positioning accuracy, vibration associated with reciprocating movement, and reduced durability of the belt as result of contact with the flange on the pulley's side face. The core cord twist angle of the helical synchronous belt is set to a value opposing to the helical tooth angle, with the helical tooth angle set to 5° to 15°, and core cord twist angle set to 15° to 2°.